

## 自由度の高い平鋼管選択

### 鋼管の外形・厚さの標準寸法

外径 (mm)	標準管厚(mm)																			
	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
600	○	○	○	○	○	○	○	○	○	○	○									
650	○	○	○	○	○	○	○	○	○	○	○	○								
700	○	●	●	●	●	●	●	●	●	●	●	●	●	●						
750	○	○	●	●	●	●	●	●	●	●	●	●	●	●	●					
800	○	○	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
850	○	○	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
900	○	○	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
950	○	○	○	○	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
1000	○	○	○	○	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
1050	○	○	○	○	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
1100	○	○	○	○	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
1150	○	○	○	○	○	○	●	●	●	●	●	●	●	●	●	●	●	●	●	●
1200	○	○	○	○	○	○	●	●	●	●	●	●	●	●	●	●	●	●	●	●
1250		○	○	○	○	○	●	●	●	●	●	●	●	●	●	●	●	●	●	●
1300		○	○	○	○	○	●	●	●	●	●	●	●	●	●	●	●	●	●	●
1350		○	○	○	○	○	○	○	●	●	●	●	●	●	●	●	●	●	●	●
1400		○	○	○	○	○	○	○	●	●	●	●	●	●	●	●	●	●	●	●
1500			○	○	○	○	○	○	●	●	●	●	●	●	●	●	●	●	●	●
1600			○	○	○	○	○	○	●	●	●	●	●	●	●	●	●	●	●	●
1700				○	○	○	○	○	○	○	●	●	●	●	●	●	●	●	●	●
1800				○	○	○	○	○	○	○	●	●	●	●	●	●	●	●	●	●
1900					○	○	○	○	○	○	●	●	●	●	●	●	●	●	●	●
2000					○	○	○	○	○	○	●	●	●	●	●	●	●	●	●	●
2100						○	○	○	○	○	●	●	●	●	●	●	●	●	●	●
2200						○	○	○	○	○	●	●	●	●	●	●	●	●	●	●
2300							○	○	○	○	○	○	○	●	●	●	●	●	●	●
2400								○	○	○	○	○	○	○	○	●	●	●	●	●
2500									○	○	○	○	○	○	○	●	●	●	●	●

注) SKK400、SKK490 は鋼管径 600mm～2500mm、STK400、STK490 は鋼管径 600mm～1016mm、STKN400W、STKN400B、STKN490B は鋼管径 600mm～1574.8mm、KHP550 は鋼管径 600～1200mm を用いることが可能

○：鋼管・鉄筋同時建込み工法に使用可

●：ケーシング併用工法、鋼管・鉄筋同時建込み工法に使用可